

- Professional Grade Heavy Duty Steel Construction
 - Heavy Duty CNC Robotically Spun & Ribbed Discs with Rolled Edges
- MADE IN USA



P Series 50' Spring Driven Hose Reels

- Machined Solid Brass 90° Full-Flow NPT Swivel
- Lubricated & Enclosed Cartridge-Style Motor
- 1/4" Steel Base, Sturdy Single Pedestal
- Multi-Position Guide Arm • Adjustable Solid Rubber Hose Stop
- Long Lasting, Chip Resistant & Rust Inhibiting CPC Powder Coat Finish
- Sturdy Permanently Lubricated Precision Bearings

CXP-LP-150 1/4" ID 1/2" OD, 300 PSI SRP **\$418.60**
CXP-LP-350 3/8" ID 5/8" OD, 300 PSI SRP **\$460.35**

EZ-Coil Model

- Controlled Retraction Speed up to 80% Slower

CXEZ-P-LP-350 3/8" ID 5/8" OD, 300 PSI SRP **\$548.04**

PC10 Series 30' Spring Driven Cord Reels

INDOOR USE ONLY

- 20A, 115V 60 Hz Single Phase; 12/3 AWG SJO
- Non-Corrosive, High Strength CoxComposite™ Ratchet Hub with Self-Lubricating Bronze Bearings
- Solid 1-Piece, 12GA Steel Base & Support Post
- CoxComposite™ Grommet with Continuous Radius Design
- Chip Resistant & Rust Inhibiting CPC Powder Coat Finish
- Adjustable Solid Rubber Cord Stop
- 5' Lead Cable & Grounding Plug



CXPC10-3012-A SRP **\$634.67**
Single Industrial Receptacle

CXPC10-3012-B SRP **\$750.54**
Quad "4 Plug" Industrial Receptacle



Compact Hand Crank Hose Reels

ALL REELS SUPPLIED LESS HOSE

- Adjustable Tension Brake
- High Quality Steel Construction
- Long Lasting, Chip Resistant & Rust Inhibiting CPC Powder Coat Finish



100 Series

- 4000 PSI • Solid 1-Piece Heavy Gauge All Steel "U" Shaped Frame
- Machined Solid Brass 90° Full-Flow NPT Swivel
- Direct Hand Crank Rewind

CX112-3-100 100' 3/8" ID, 5/8" OD SRP **\$257.84**
CX117-3-250 250' 3/8" ID, 5/8" OD SRP **\$296.46**

1125 Series

- 3000 PSI • 1-Piece All Welded 12 Gauge Steel "A" Frame Base
- Electroless Nickel Plated Steel 90° Full-Flow NPT Swivel Inlet
- Exclusive Low Profile Outlet Riser & Open Drum Slot Design
- Front Bevel Geared Crank Retraction

CX1125-5-100 100' 3/4" ID, 1 1/4" OD SRP **\$490.61**
CX1125-5-175 175' 3/4" ID, 1 1/4" OD SRP **\$509.40**

CXC-L350-5016-A C "Combination" Air-Electric Series 50' Spring Driven Cord Reel

INDOOR USE ONLY

- 3/8" ID, 5/8" OD; 13 Amps, 300 Max PSI; 16/3 AWG 50' SJO
- 2 Reel Assembly for Dual Hose Applications, each Reel Operates Independently
- Machined from Solid Brass 90° Full-Flow NPT Swivel
- Lubricated & Enclosed Cartridge-Style Motor
- 1/4" Steel Base, Sturdy Single Expanded Pedestal Design
- Multi-Position Guide Arm, Adjusts to Wall, Floor & Overhead
- Multi-Position Lock Ratchet Mechanism • Adjustable Rubber Stop
- 5' Lead Cable & Grounding Plug • Single Industrial Receptacle



SRP **\$1,063.70**



RLCTW74500LPT

1/4" x 50' Twin Line Welding Hose Reel T-Grade

- 7000 Series; 1/4" ID, 0.53" OD; 200 PSI; 150°F Max
- Leak Prevention - Double Sealed, Special Molded O-Rings
- Individually Powder-Coated Components
- Reinforced Steel, Robotically Welded Steel Base
- Aluminum Independent Dual Swivel Body



CALL FOR PRICE

50' Premium Duty Spring Retractable Air Hose Reels

- 300 PSI • 150°F Max Temp • Hose is Plumbed into Base
- 50' Low-Pressure PVC Hose; Hose for Air or Water Service ONLY
- Individually Powder-Coated Steel Components

5005 Series

- Bent Tube Swivel Design • Swivel Nested Inside Spool
- Base Plate & Upright Constructed from 14 Gauge Steel; Guide Arm is 13 Gauge & Spool is 16 Gauge Steel
- Reliable Speed Latch Allows for Positive Locking of Spool in 2 Positions per Rotation
- Guide Arm Adjusts to 2 Positions • Robotically Welded Steel Base

RLC56500LP 3/8" ID, 0.60" OD

CALL FOR PRICE

RLCA58500LP 1/2" ID, 0.75" OD SHOWN

CALL FOR PRICE

7000 Series

RLC78500LP 1/2" ID, 0.75" OD

CALL FOR PRICE

- Base Plate, Upright & Guide Arm Constructed from 11 Ga Steel; Spool is 16 Ga Steel
- Guide Arm Adjusts to 7 Positions

