# AO2225 5" High Speed Sander

- 18,000 RPM, 7/16"-20" Spindle Thread Size
- 1/4" NPT, 3/8" I.D., 4 CFM, 90-120 PSI
- High-Speed, Vibration-Free
- Performance
- Lightweight Pistol Grip Design
- Built-In Regulator for Positive Speed Control
- Direct Drive Motor with Handle Exhaust
- Includes: 3" & 4<sup>1</sup>/<sub>4</sub>" Phenolic Backing Pad & Hub Wrench

# USER \$63.53 SRP **\$41.95**

# A09425 **Dual Temperature** Heat Gun Kit

- Switch for 2 Different Heat Settings: 572°F Low, 932°F High
- 12.5A, 120V. 60 Hz
- Air Volumn: 10 сғм Low, 17 сғм High
- Wattage: 1000W Low, 1500W High
- Double Insulation for Extra Safety
  Low Noise & Vibration Design • Includes: Dual Temperature Heat Gun, Large Deflector Nozzle,
- Reduction Nozzle, Small Deflector Nozzle, Reflector Nozzle & Blow Molded Case

USER \$47.40 SRP \$31.02

# AOADN38 **XL Rivet Nut Drill Adapter Kit**

- Easily Convert Cordless or Corded
- Drills into Power Rivet Nut Setters • Use 12V & up Cordless Drills for Aluminum & Steel Rivet Nuts, or 18V+ for Larger Sizes like

M10 & 3/8" and/or Stainless (Drills must Feature Torque Limiting Clutch)

- 1/4" Hex Shank Size Low Speed (<240 RPM)
- CNC Machined from Solid Billet Aluminum & Features Durable Bearings CR-MO Mandrels
- Includes: 8 Mandrels & Nosepieces in Metric & SAE: M5, M6, M8, M10, 10-24, 1/4-20", 5/16-18", 3/8-16"

USER \$157.35 SRP \$99.88

Lever Throttle for Feathering Control

### **AOT20AH** <sup>1</sup>/<sub>4</sub>" 90° Angle

• 20,000 RPM <u>Front</u> Exhaust, <sup>1</sup>/з нр, 3 сFM

USER \$86.13 SRP \$55.40

## AOT210 1/4" Medium with Japanese Bearings

- 22,000 RPM Rear Exhaust
- 1/2 HP. 4 CFM Rib Textured Handle

USER \$50.65 SRP **\$33.16** 



#### Nano Impact Sockets Forged CR-MO with Superior Material Thickness

Between Socket Body & Drive

### A078215 15-Pc 1/2" Dr Metric SHOWN

- 1.10" Long (28мм) 22мм (<sup>7</sup>/в") Outside Hex
- Includes: 1 Aluminum Socket Holder & Impact Sockets in Sizes. 10мм - 24мм

for 1/2" Dr Nano Style Impact Sockets with 22мм Outside Hex

• Maximum Peak Torque Durability to Match Larger 1/2" Drive

• Maintains Low Profile Working Height of 1.10" with Sockets

USER \$48.75 SRP **\$34.21** 

#### USER \$85.98 SRP **\$55.75** . . . . . . . . . . . . . . .

#### A078314 14-Pc <sup>3</sup>/8" Dr Metric

- 0.88" Long (22.5мм) 17мм Outside Hex
- Includes: 1 Aluminum Socket Holder & Impact Sockets in Sizes, 6мм - 19мм

# USER \$58.30 SRP **\$38.53**

### A078319

A078218

Flex Head

100-Tooth Ratchet

Socket Sizes

Installed

18" Extra-Long

**Ratchet Wrench** 

#### 19-Pc <sup>3</sup>/<sub>8</sub>" Dr 6-Pt Low Profile Metric, No Skips

• 0.88" Long (22.5мм) • 17мм Outside Hex • Includes: 1 Aluminum Socket Holder & Impact Sockets in Sizes, 6мм - 24мм

# USER \$91.85 SRP \$64.46

# AO3018 3.5" Digital **Tire Inflator**

with 21" Stainless Hose

- 3 175 psi, 0.1 psi Resolution
- 32°F 104°F Working Temperature
- Works with Nitrogen & CO<sup>2</sup> Systems
- Large Face LCD Digital Read-Out Displays KFG. BAR. PSI. KPA Measurements
- LCD Back Light & Covered with Rubber Sleeve
- 1 Button Operation, Auto Shut Off in 90 Seconds
- 2 Position Lever, Deflate/Inflate Easy Change Chuck System
- Dual AAA Battery Powered Design, Batteries Included

USER \$130.00 SRP **\$87.72** 











